



PRIMO Melter Reference Guide



1.888.SoapMelters(762.7635) • SoapMelters.com

PRIMO Model	Approximate (Gal/L) Capacity (LB/KG)	ID = Inner Dimensions OD = Outer Dimensions	Electrical Specifications
2000	1957 Gal / 7412 L	ID: 80"(203cm) Diameter x 90"(229cm) Deep	17,400W 220v 80amps
	15000 LB / 6804 KG	OD: 84"(213cm)L x 84"(213cm)W x 92"(234cm)H	
1500	1566 Gal / 5927 L	ID: 80"(203cm) Diameter x 72"(183cm) Deep	14,800W 220v 68amps
	12000 LB / 5448 KG	OD: 84"(213cm)L x 84"(213cm)W x 74"(187cm)H	
1200	1268 Gal / 4799 L	ID: 72"(183cm) Diameter x 72" (183cm) Deep	12,200W 220v 56amps
	10000 LB / 4550 KG	OD: 76"(193cm)L x 76"(193cm)W x 74"(187cm)H	
1000	950 Gal / 3596 L	ID: 68"(173cm) Diameter x 60" (153cm) Deep	10,800W 220v 50amps
	7500 LB / 3405 KG	OD: 72"(183cm)L x 72"(183cm)W x 62"(157cm)H	
700	685 Gal / 2593 L	ID: 60"(153cm) Diameter x 56" (143cm) Deep	8,200W 220v 38amps
	5000 lbs / 2270 kg	OD: 64"(163cm)L x 64"(163cm)W x 58"(1147cm)H	
300	316 Gal / 1196 L	ID: 46"(117cm) Diameter x 44" (112cm) Deep	3,200W 220v 15amps
	2054 lbs / 932 kg	OD: 48"(122cm)L x 48"(122cm)W x 46"(117cm)H	
200	216 Gal / 818 L	ID: 38"(97cm) Diameter x 44" (112cm) Deep	3,200W 220v 15amps
	1675 lbs / 760 kg	OD: 40"(102cm)L x 40"(102cm)W x 46"(117cm)H	
150	158 Gal / 598 L	ID: 36"(92cm) Diameter x 36" (92cm) Deep	1,800W 120v 15amps
	1226 lbs / 556 kg	OD: 38"(97cm)L x 38"(97cm)W x 38"(97cm)H	
100	110 Gal / 416 L	ID: 30"(76cm) Diameter x 30" (76cm) Deep	1,600W 120v 14amps
	770 lbs / 349 kg	OD: 32"(82cm)L x 32"(82cm)W x 32"(82cm)H	
75	76 Gal / 287 L	ID: 30"(76cm) Diameter x 25" (64cm) Deep	1,500W 120v 13amps
	532 lbs / 241 kg	OD: 32"(82cm)L x 32"(82cm)W x 27"(69cm)H	
50	49 Gal / 185 L	ID: 20"(51cm) Diameter x 36" (92cm) Deep	1,200W 120v 10amps
	367 lbs / 166 kg	OD: 22"(56cm)L x 22"(56cm)W x 38"(97cm)H	
35	33 Gal / 125 L	ID: 18"(46cm) Diameter x 30" (76cm) Deep	900W 120v 8amps
	264 lbs / 120 kg	OD: 20"(51cm)L x 20"(51cm)W x 32"(82cm)H	
25	26 Gal / 98 L	ID: 18"(46cm) Diameter x 24" (61cm) Deep	800W 120v 7amps
	169 lbs / 76 kg	OD: 20"(51cm)L x 20"(51cm)W x 26"(66cm)H	
15	15 Gal / 57 L	ID: 15"(38cm) Diameter x 20" (51cm) Deep	800W 120v 7amps
	105 lbs / 47 kg	OD: 17"(43cm)L x 17"(43cm)W x 22"(56cm)H	
10	11 Gal / 41 L	ID: 15"(38cm) Diameter x 15" (38cm) Deep	800W 120v 7amps
	77 lbs / 35 kg	OD: 17"(43cm)L x 17"(43cm)W x 17"(43cm)H	
7	7 Gal / 26 L	ID: 15"(38cm) Diameter x 10" (25cm) Deep	800W 120v 7amps
	56 lbs / 23 kg	OD: 17"(43cm)L x 17"(43cm)W x 12"(30cm)H	
3	3.5 Gal / 13 L	ID: 10"(25cm) Diameter x 10" (25cm) Deep	300W 120v 3amps
	25 lbs / 11 kg	OD: 12"(30cm)L x 12"(30cm)W x 12"(30cm)H	

All Units: 304 Grade,#4 Polished Stainless Steel; Digitally Controlled Temperature up to 212F/100C
Options: 220v, Stainless Steel Legs and Wheels, Custom Sizes, Multiple Valves & Heating to 400°F/204°C

*SoapMelters reserves the right to modify any of the above values

Copyright ©2008 Melting And Filling Equipment Inc. All Rights Reserved